

# LANmark-OF Tight Buffer Universal Cca

LANmark-OF Tight Buffer Universal 6x Multimode 50/125 OM4 LSZH  
Cca Aqua

## Contact

sales  
Phone: +49 2166 27 2220  
datanetworks.de@nexans.com

Nexans Ref.: N167.TBUN06-AC

- Tight Buffer Universal optical fibre cable
- Indoor cable and outdoor installation in a duct
- Fully waterproof and rodent retardant
- Designed for direct termination and splicing
- 6 fibres OM4

## DESCRIPTION

### Description and Application

The LANmark-OF Tight Buffer Universal cable is a fibre cable that can be used indoor and outdoor in a duct.

It complies with the indoor fire requirements and can be installed indoor both vertically and horizontally.

The LANmark-OF Tight Buffer Universal can also be used for outdoor installation in a duct: the water tight glass yarns make the cables fully waterproof and rodent retardant.

The LANmark-OF Tight Buffer Universal cable has 900 um buffered fibres. This second coating till 900 um provides additional protection of the fibres and facilitates the handling when terminating the fibres in a patch panel. The easy strip tight buffer design allows stripping the fibre over 10 cm in one action.


The LANmark-OF Tight Buffer Universal is most suitable for direct termination by either anaerobic or hot melt connectors. The tight buffered fibres can also be terminated with splicing of pigtailed.

Tight buffer cables are available in Aqua for OM3 and OM4 and Yellow for singlemode. High exposure to UV radiation and sunlight could lead to fading of the Aqua and Yellow jacket, but the mechanical integrity of the cable jacket will be maintained.

### Construction

Legend accompanying the cross section drawing:

1. LSZH outer sheath with UV resistant additive
2. Watertight glass yarns
3. Optical fibres (900 um)
4. Central strength element



**LANmark-OF**

## DECLARATION OF PERFORMANCE

Cca-s1a,d1,a1

## STANDARDS

International ISO/IEC 11801



Mechanical resistance to impacts  
10 impacts of 3 N.m



Flame retardant  
IEC 60332-1



Fire retardant  
IEC 60332-3



Gases toxicity  
IEC 61034



Gases corrosivity  
IEC 60754-1, IEC 60754-2



Ambient installation  
T°C range  
0 - 40 °C



Static bending rad.  
55 mm



Min. dynamic operating bending rad.  
85.0 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 5/20/22 www.nexans.de Page 1 / 2

## Characteristics

- Designed for direct termination and splicing
- Dielectric design
- Indoor cable for horizontal and vertical installations
- Fire performance compliant with IEC 60332-1, IEC 60332-3, IEC 60754-1, IEC 60794, IEC61034
- Outdoor installation in a duct
- Fully waterproof
- Rodent retardant
- UV resistant
- Available in SM, OM3 and OM4
- Available in 6-12 and 24 fibres

## CHARACTERISTICS

### Construction characteristics

Fiber optic type	OM4 50/125
------------------	------------

### Dimensional characteristics

Nominal outer diameter	5.3 mm
Approximate weight	33 kg/km
Number of optical fibres	6

### Mechanical characteristics

Maximum pulling force (IEC 60794-1-2-E1)	700 N
Maximum operating pulling force	200 N
Crush resistance (IEC 60794-1-E3)	100 N/cm
Mechanical resistance to impacts	10 impacts of 3 N.m

### Usage characteristics

Flame retardant	IEC 60332-1
Fire retardant	IEC 60332-3
Gases toxicity	IEC 61034
Gases corrosivity	IEC 60754-1, IEC 60754-2
Ambient installation temperature, range	0 - 40 °C
Minimum static operating bending radius	55 mm
Minimum dynamic operating bending radius	85.0 mm
Operating temperature, range	-20 - 70 °C
Storage temperature, range	-40 - 70 °C



Mechanical resistance to impacts  
**10 impacts of 3 N.m**



Flame retardant  
**IEC 60332-1**



Fire retardant  
**IEC 60332-3**



Gases toxicity  
**IEC 61034**



Gases corrosivity  
**IEC 60754-1, IEC 60754-2**



Ambient installation T°C range  
**0 - 40 °C**



Static bending rad.  
**55 mm**



Min. dynamic operating bending rad.  
**85.0 mm**