

iGigaSwitch 16xx E+ HW5 Series

Contact

Nexans LAN Systems

Tel.: +49 (0) 2166 27 2220

sales.ans@nexans.com

www.nexans.com/LANactiveIndustry

LANactive Industry 16 Port Managed Full Gigabit Ethernet Switch

- 16 ports in total, variable number of SFP ports
- Up to 12x PoE ports with max. 360W power budget
- Optionally with integrated I/O module
- IEC 61850 compliancy is tested and certified by KEMA/DNV-GL
- Wide operating temperature range: -40 ... +85°C

Description

Nexans managed Industrial Ethernet iGigaSwitch 16xx E+ HW5 family is part of Nexans *LANactive Industry* product portfolio and designed for installing robust and reliable networks in harsh environments. *LANactive Industry* iGigaSwitch 16xx E+ HW5 family is designed to provide maximum network availability, security, longest lifetime in harsh environments and making the network maintenance easier. The iGigaSwitch 16xx E+ HW5 family provides great flexibility in network design - it has 16 Gigabit ports including 2, 4, 8 or 12 SFP ports. The iGigaSwitch is designed for DIN-Rail mounting and comes with an external power supply to operate in the needed power range.

I/O interfaces

The optionally I/O interfaces of the iGigaSwitch 16xx allows a fast, simple and low-cost integration of non-IP based devices directly e.g. different sensors, controllers, buttons etc. The iGigaSwitch is offering extensive management functionalities with interactions, sending of messages as well as the activation of alarms.

Power over Ethernet (PoE/PoE+)

Up to 12x connected devices can be supplied with Power over Ethernet. In accordance with the latest IEEE 802.3at (PoE+) standard, up to 30W are available for each connected device, with total budget of 360Watts.

IEC 61850

Nexans iGigaSwitch family comply to IEC 61850 requirements (parts 6, 7-1, 7-2, 7-3, 7-4, 8-1, 9-1 and 9-2 Communication networks and systems for power utility automation). This functionality is critical for Smart grid and allows to use standardized equipment to ensure correct and reliable communication of all networked devices of Smart grid infrastructure (including switches, PLCs, different controllers, sensors etc.) with each other and with central SCADA.

The compliance is tested and confirmed by KEMA/DNV-GL.



Made in Germany

LANactive Industry



Standards (extract)

IEEE 802.3
IEEE 802.3u
IEEE 802.3ab
IEEE 802.3af
IEEE 802.3at
IEEE 802.3z
IEEE 802.3x
IEEE 802.1AB
IEEE 802.1D
IEEE 802.1Q
IEEE 802.1X
IEEE 802.1AX
IEEE 802.3ad

IEC 61850-6, 7-1, 7-2, 7-3, 7-4, 8-1, 9-1, 9-2
IEC 61850-3



Designed for harsh environments



PoE/PoE+



Compact Design



Interoperability



Easy Maintenance



Redundancy



Security and Reliability



High Availability

iGigaSwitch 16xx E+ HW5 Series

Contact

Nexans LAN Systems
Tel.: +49 (0) 2166 27 2220
sales.ans@nexans.com
www.nexans.com/LANactiveIndustry

Hardware Features

Ordering Information	iGigaSwitch 1604 E+ SFP-4VI HW5	iGigaSwitch 1608 E+ SFP-8VI HW5	iGiga Switch 1612 E+ SFP- 12VI HW5
Article Number	88306504	88306508	88306512
LAN Interfaces			
User Ports (Twisted Pair)	12x 10/100/1000Mbps	8x 10/100/1000Mbps	4x 10/100/1000Mbps
Uplink Ports (SFP)	4x 100/1000Mbps	8x 100/1000Mbps	12x 100/1000Mbps
Power over Ethernet			
Max. Number of PoE+ Ports	12	8	4
Max. PoE Power Budget	360W	240W	120W
PoE Mode	30W per Port, Mode A, Pin 1-2/3-6		
Diagnostic Functions (Interfaces)			
Digital Diagnostics Monitoring Interface	Yes		
Twisted Pair Cable Diagnostic	Yes		
General			
Dimensions [WxHxD]	95mm x 184mm x 125mm		
IP Protection Class	IP30 (EN 60529)		
Mounting	35mm DIN-Rail Mounting according to EN 60715, (EN 50022) Different mounting positions of DIN-Rail clip - vertical and horizontal switch mounting. Optional: wall mounting.		
Material	Anodised/Varnished Aluminium		
Colour	Black		
Ambient Temperature	Operation: -40 ... 85°C, Storage: -40 ... 85°C		
Relative Humidity	20 - 90% (non-condensing)		
Weight	1800g		
MTBF	> 500,000h		
Power Supply			
Input voltage for switch	18 ... 60V DC		
Input voltage for PoE+	46 ... 57 V DC (typ. 54V DC)		
Power consumption (without PoE)	13W (standby) ... 15W (typ.) ... 28W (fully connected)		
Heat output	52 BTU(IT)/h (typ.)		
Connector	2x 3-pin terminal blocks, screw-on type (up to 2.5 mm ²) / (+) (-) (FPE)		
Connector PoE	3-pin terminal blocks, screw-on type (up to 2.5 mm ²) / (+) (-) (FPE)		

iGigaSwitch 16xx E+ HW5 Series

Contact

Nexans LAN Systems
Tel.: +49 (0) 2166 27 2220
sales.ans@nexans.com
www.nexans.com/LANactiveIndustry

Software Features

Switching Parameters

Switching Type	Store-and-Forward, self-learning
Max. Frame Size	9,600 Bytes (Support of Jumbo frames)
Packet Buffer	512 kBytes
Latency (RFC1242)	100 Mbps / 64 Byte (FIFO/LIFO) 9µs / 3.9µs 100 Mbps / 1518 Byte (FIFO/LIFO) 125µs / 4µs 1000 Mbps / 64 Byte (FIFO/LIFO) 2.7µs / 2.2µs 1000 Mbps / 1518 Byte (FIFO/LIFO) 15µs / 2.5µs
MAC-Address Table	8,192 MAC-Addresses
VLANs	IEEE802.1q with up to 256 Groups
Quality of Service Layer 2	IEEE802.1p Class of Service (4 Queues per Port)
Quality of Service Layer 3	RFC2474/3168 DSCP (4 Queues per Port)
Bandwidth Limitation	Bitrate and Number of Packets
Fabric Attach	Basic Fabric Attach Client Support

Management

	On-Board High-Performance Management
LEDs	Management, Port Status and Activity, Memory Card
Zero-Touch Configuration	Via NEXMAN Controller
IP-Address	IPv4, IPv6
DHCP-Client	DHCP, DHCPv6
DHCP Relay Agent	Yes
File Transfer	TFTP, SCP
Console Port	V.24 with Nexans Console Cable
Web-Interface	HTTP, HTTPS
Command Line Interface	SSH, Telnet
SNMP	SNMPv1, v2c, v3
Further Management Protocols	Syslog, LLDP, LLDP-MED, CDP
Time Synchronisation	SNTP
Port Statistics	Detailed per Port

Redundancy

Redundancy Protocols	STP, RSTP, MSTP, MRP
Link Aggregation	LACP

Security

Password Protection	Two Access Levels (R/W or R/O)
Authentication via Radius	CLI and NEXMAN
Authentication via TACACS+	CLI and NEXMAN
ACL for Management Interface	Up to 16 Access Control Lists
Portsecurity via MAC-Address	Up to 3 predefined MAC-Addresses
Portsecurity via Radius	IEEE802.1x
DHCP Snooping	Yes
Loop and Broadcast Limiter	Yes
Firmware Update	Dual Firmware Image
Configuration Button	Yes (configuration button deactivatable)
Reset Button	Yes (configuration button deactivatable)
Memory Card	Micro SD-Card, optionally with fixed MAC-Address

iGigaSwitch 16xx E+ HW5 Series

Contact
Nexans LAN Systems
Tel.: +49 (0) 2166 27 2220
sales.ans@nexans.com
www.nexans.com/LANactiveIndustry

Standards

Standards

Electrical safety (IT equipment)	EN 60950
Electrical conditions (EMC)	EN 55022
Communication networks and systems for power utility automation	IEC 61850-6, 7-1, 7-2, 7-3, 7-4, 8-1, 9-1 and 9-2 IEC 61850 Certificate Level A IEC 61850 SERVER functionality - MMS and GOOSE KEMA/DNV-GL certified
General environmental requirements for hardware design	IEC 61850-3
Environmental Standards for Networking Devices Installed in Power Utility Substations	IEEE 1613
Immunity for industrial environments	IEC 61000-6-2
Adjustable speed electrical power drive systems	IEC 61800-3

Dimensions

